



**UDI Barcode
Asset Identification**



**Permanent
Signage**




**Medical Device
Control Panels**

THE TECHNOLOGY:

ANODIZED LAYER

The glass-clear, sapphire-hard anodized layer resists chemicals, paint, abrasion and dirt.



SEALED IMAGE

The image is absorbed into the pores.

ALUMINUM LAYER

The rigid aluminum base won't peel, crack or delaminate.

EXCEPTIONALLY DURABLE. WIDELY SPECIFIED. ALWAYS READABLE.

Anodized aluminum has long been a standard for sterilization containers, control panels and other identification products in the surgical field. Metalphoto photosensitive anodized aluminum improves that standard by being resistant to heat, chemicals and harsh cleaning solvents. Ideal for sterile environments, Metalphoto does not harbor bacteria or corrode after thousands of sterilization cleaning cycles.

Metalphoto complies with several medical labeling requirements including AAMI/CDV-1 ST79:2010/A2.06, a comprehensive guide to steam sterilization and sterility assurance, and the FDA Amendments Act of 2007 for the establishment of a Unique Device Identification (UDI) System.

Metalphoto of Cincinnati has been a leading full-service manufacturer of durable custom identification products for more than 50 years. Contact MPC for the best solution to your equipment identification needs.

PRODUCT BENEFITS

EXCEPTIONALLY DURABLE:






- + UV-stable image is permanently sealed within the anodized aluminum.
- + Virtually impervious to chemicals, heat, abrasion, salt spray and sunlight.
- + Certified for 20 year plus outdoor applications.
- + Earned more top scores than any other IUID barcode label material tested by the U.S. Navy (NSWC, Corona Division, IUID Center; August 2011).

WIDELY SPECIFIED:

- + Meets a wide array of commercial, government and military specifications.
- + Notable certifications include: MIL-STD-130N, STANAG 2290, GGP-455B(3) Type I, MIL-DTL-15024F, MIL-P-19834B and A-A-50271 (several others listed on metalphoto.com).

PHOTOGRAPHIC RESOLUTION:

- + Photographic image affords extreme detail and contrast at any size.
- + Anti-counterfeit security printing is available.

-  **UV STABLE**
-  **ABRASION RESISTANT**
-  **TEMPERATURE RESISTANT**
-  **FLUID RESISTANT**
-  **RECYCLABLE**

PERFORMANCE CHARACTERISTICS

Because of its ability to perform across a range of challenging environments, Metalphoto meets an array of government, industrial and military specifications. Visit www.metalphoto.com for a list of specifications for which Metalphoto is qualified.

CHARACTERISTIC	RESULT
Abrasion Resistance	No pronounced image loss, degradation or reduced readability after 7,000 cycles on an abrading wheel.
Acid Corrosion	No deterioration or image degradation after 24 hours in 3% nitric acid.
Heat Resistance	No legibility loss or degradation when subjected to 1,000°F.
Salt Spray Corrosion	No deleterious effect after a 720-hr salt spray (fog) test. 2,6 "Very Good" corrosion resistance after 113 days seawater exposure.
Accelerated Light and Weather Resistance	No pronounced deterioration of legibility after 400-hr carbon arc weatherometer exposure. (≈ 20+ year outdoor life)
Accelerated Oxygen Aging	No discoloration or fading after 96-hr/300 psi/ 70°C oxygen bomb aging
Stain Resistance	No black fading when plates are exposed to tincture of iodine.
Cleaning Resistance	No deleterious effects when tested with alkaline cleaners (MILC- 87937 or equivalent) for aircraft surfaces.
Low Temperature Resistance	No deleterious effect or image fade after 1 hour at -50°F. No impairment of legibility upon exposure at -67°F.
Organic Solvent Resistance	No softening, staining or noticeable fade after 24-hr exposure to: JP-4 fuel, Gasoline, Mineral Spirits, Methyl Ethyl Ketone, Turpentine, Turbine & Jet Fuel, Kerosene, Xylo, Acetone, Toluol, Heptane, Trichlorethylene, MIL-H-5606 Hydraulic Fluid and MIL-L-7808 Jet Engine Oil.
Fungus Resistance	Visual reading of "0" per ASTM-G21.
Thermal Shock	No deterioration after 3 cycles between -65°C and 125°C
Moisture Resistance	No deterioration after 10 humidity cycles per MIL-STD-202, method 106.

TECHNICAL SPECIFICATIONS

MATERIAL: Anodized Aluminum

SIZES: Up to 24" x 40"

THICKNESSES: .003", .005", .008", .012", .020", .032", .039", .063", .090", .125"

FINISHES:



MATTE
non-reflective
with dull finish



SATIN
semi-gloss medium
reflective material



4
brushed to resemble
a stainless steel finish



GLOSS
highly reflective,
mirror-like

CONTACT MPC

Call **1-800-528-4058** or visit our website at **MPofCinci.com**

*Metalphoto of Cincinnati does not warrant the performance of its materials in any environment.
Metalphoto is a registered trademark of Horizons Incorporated.

Ver. 1.0 APRIL 2014